

P801	PACKING INSTRUCTION	P801
This instruction applies to UN Nos. 2794, 2795 or 3028.		
The following packagings are authorized, provided that the provisions of 4.1.1.1 , 4.1.1.2 , 4.1.1.6 , and 4.1.3 are met:		
(1) Rigid outer packagings, wooden slatted crates or pallets.		
Additionally, the following conditions must be met:		
(a) Batteries stacks must be in tiers separated by a layer of electrically non-conductive material;		
(b) Battery terminals must not support the weight of other superimposed elements;		
(c) Batteries must be packaged or secured to prevent inadvertent movement;		
(d) Batteries must not leak under normal conditions of transport or appropriate measures must be taken to prevent the release of electrolyte from the package (e.g. individually packaging batteries or other equally effective methods); and		
(e) Batteries must be protected against short circuits.		
(2) Stainless steel or plastics bins may also be used to transport used batteries.		
Additionally, the following conditions must be met:		
(a) The bins must be resistant to the electrolyte that was contained in the batteries;		
(b) The bins must not be filled to a height greater than the height of their sides;		
(c) The outside of the bins must be free of residues of electrolyte contained in the batteries;		
(d) Under normal conditions of transport, no electrolyte may leak from the bins;		
(e) Measures must be taken to ensure that filled bins cannot lose their content; and		
(f) Measures must be taken to prevent short circuits (e.g. batteries are discharged, individual protection of the battery terminals, etc.).		

P802	PACKING INSTRUCTION	P802
The following packagings are authorised, provided the general provisions of 4.1.1 and 4.1.3 are met:		
(1) Combination packagings		
Outer packagings: 1A1, 1A2, 1B1, 1B2, 1N1, 1N2, 1H1, 1H2, 1D, 1G, 4A, 4B, 4N, 4C1, 4C2, 4D, 4F, 4G or 4H2; maximum net mass: 75 kg.		
Inner packagings: glass or plastics; maximum capacity: 10 litres.		
(2) Combination packagings		
Outer packagings: 1A1, 1A2, 1B1, 1B2, 1N1, 1N2, 1H1, 1H2, 1D, 1G, 4A, 4B, 4N, 4C1, 4C2, 4D, 4F, 4G or 4H2);		
maximum net mass: 125 kg.		
Inner packagings: metal; maximum capacity: 40 litres		
(3) Composite packagings: Glass receptacle in steel, aluminium or plywood drum (6PA1, 6PB1 or 6PD1) or in a steel, aluminium or wood box or in wickerwork hamper (6PA2, 6PB2, 6PC or 6PD2) or in solid plastics packaging (6PH2); maximum capacity: 60 litres.		
(4) Steel drums (1A1) with a maximum capacity of 250 litres.		
(5) Pressure receptacles may be used provided that the general provisions of 4.1.3.6 are met.		
Special packing provision:		
PP79	For UN 1790 with more than 60% but not more than 85% hydrogen fluoride, see P001	